
Sensor-switched LED floodlight

Spot Garden

Sensor Connect EAN 4007841 058685 Article number 058685









20.000 h



















Function description

Interconnected garden enjoyment. The Spot Garden Sensor Connect ground spotlight with 90° infrared sensor simply pushes into the earth and provides versatile illumination all around the home. The LED spot is conveniently set, interconnected and controlled via Bluetooth by app. ON and OFF times, twilight and time settings as well as creating lighting group – all not a problem. 520 lm, 7 W, 3000 K. Includes 2.5 m mains plug and GU-10 LED.

Technical specifications

Dimensions (L x W x H)	140 x 69 x 369 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Sensor Technology	passive infrared
Output	7 W
Power consumption	0,5 W
Interconnection	Yes
Slave modeselectable	Yes
Luminous flux	520 lm
Colour temperature	3000 K
Colour variation LED	SDCM5
Farbwiedergabeindex	80-89
With lamp	Yes, LED lamp
Lamp	LED can be replaced
With motion detector	Yes
Detection angle	90 °
Angle of aperture	90 °
Sneak-by guard	No
Capability of masking out individual segments	No
Reach, radial	$r = 2 \text{ m } (3 \text{ m}^2)$
Reach, tangential	r = 10 m (79 m²)

Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s - 60 Min.
Basic light level function	No
Main light adjustable	No
Functions	Digital timer, Master/slave override
Settings via	Bluetooth
Soft light start	No
Continuous light	selectable, 4h
Impact resistance	IK03
IP-rating	IP44
Protection class	II
Ambient temperature	-20 - 40 °C
Housing material	Aluminium
Cover material	Plastic, transparent
Manufacturer's Warranty	3 years
Includes corner wall mount	No
PU1, net weight	0,71 kg
Version	Sensor Connect
PU1, EAN	4007841058685


Sensor-switched LED floodlight

Spot Garden

Sensor Connect EAN 4007841 058685 Article number 058685



Detection Zone



Mögliche Montagehöhe: Orange: radlal
Schwarz: tangential

Dimension Drawing

